



PCB Layout Diagram
Top View

1. MATERIAL:
- a. HOUSING: LCP UL94V-0
 - b. CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: Au1u")

SEE ORDERING INFORMATION

2. ELECTRIC:
- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b. INSULATION RESISTANCE: 100 MEGA OHMS MIN
 - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d. OPERATING TEMPERATURE: -25°C ~ +85°C

ORDERING INFORMATION

BS-06-B***002

电池座系列

BS-06系列

SMT 180° TYPE

MATERIAL:

- 1A-PBT BLACK
- 1B-PA66 BLACK
- 2A-PPA BROWN
- 2B-PPA BLACK
- 3A-PPS BROWN
- 3B-PPS BLACK
- 4A-LCP WHITE
- 4B-LCP BLACK
- 5A-PA6T WHITE
- 5B-PA6T BLACK

PLATING:

- A-Au1U"
- J-Ni100U"~120U"
- K-Sn100U"~120U"

REV	DATE	DOIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION		SCALE		DESIGN CHECK	PART NO.	TITLE:
					DIM	TOL	UNIT	Fit			
					X.X	±0.25	MM	MM		2032贴片-白色电池座	Customer No.
					X.XX	±0.20		A4			
					X.XXX	±0.10		1/1	CHECK		
					ANGEL	±3°					
								PROJ.	APPROVE		

JIANGJI 苏州江基电子科技有限公司
Suzhou Jiangji Electronic Technology CO.,LTD

2032贴片-白色电池座
BS-06-B***002