



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: PBT
- b. CONTACT: BRASS
- (SURFACE PLATING: Sn100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

ORDERING INFORMATION

BS-02-A***001

电池座系列
BS-2系列
DIP 90° TYPE

PLATING:

A-Au1U"
J-Ni100U"~120U"
K-SN100U"~120U"

MATERIAL:

1A-PBT BLACK
1B-PA66 BLACK
2A-PPA BROWN
2B-PPA BLACK
3A-PPS BROWN
3B-PPS BLACK
4A-LCP WHITE
4B-LCP BLACK
5A-PA6T BLACK

JIANGJI 苏州江基电子科技有限公司
Suzhou Jiangji Electronic Technology CO.,LTD

2032黑色电池座直插

BS-02-A***001

REV	DATE	DOIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION		SCALE		DESIGN	CHECK	APPROVE	PART NO.	TITLE:
					UNIT	MM	SIZE	SHEET					
					X.X	±0.25	A4	1/1				Customer No.	
					X.XX	±0.20							
					X.XXX	±0.10							
					ANGEL	±3°							
					DIM	TOL							