



Specifications



备注(Remark)  
1.材料(MATERIAL)  
胶芯: PA9T+30%G.F UL94V-0, 颜色: 黑色  
Housing: PA9T+30%G.F UL94V-0,Color: Black  
端子: 磷/青铜, 镍底30u"MIN,表面镀金u"MIN  
Contact:Phosphor bronze,lu"MIN GOLD PLATING OVER ALL  
30u" MIN NICKEL UNDERPLATING OVER ALL

2.特性 (characteristics):  
额定电流: 1 AMP  
Raring Current:1 AMP.  
接触阻抗: 20 mΩ MAX.  
Contact Resistance: 20 mΩ MAX.  
绝缘阻抗: 1000 MΩ MIN.  
Insulating Resistance:1000 MΩ MIN.  
耐电压: AC 500V.  
Withstanding Voltage: AC 500V.  
温度范围: -40℃ to+105℃  
Temperture Range: -40℃ to+105℃



Ordering Information  
B0221-12 XX XX X AU X 1

NO. OF PINS PER ROW	Contact Plating		INSULATOR	PACKING
2~50P	Full Of Gold	Semi-gold	MATERIAL:	A:PE Bag
	G0=0.8u"	L0=0.8U"	1:PBT	B:Tape & Reel
	G1=1u"	L1=1U"	2:PA46	C:Tube
	G2=1.5u"	L2=1.5U"	3:PA66	D:Tube+CAP
	G3=2u"	L3=2U"	4:PA6T	E:Tray
	G4=3u"	L4=3U"	5:PA9T	
	G5=5u"	L5=5U"	6:LCP	
	G6=10u"	L6=10U"	7:	
	G7=15u"	L7=15U"		
	G8=20u"	L8=20U"		
	G9=30u"	L9=30U"		
	T1=Ordinary Tin Plated			
	T2=Matte Tin Plated			
	T3=Tin-plated High-temperature			
	T4=high tempreture Matt tin			



				OPERATION		SCALE		Fit	苏州瀚牧锦电子有限公司			
				X.X	±0.25	UNIT		MM				
				X.XX	±0.20	SIZE	A4	DESIGN	PART NO.		B0221-12XXXXXAUX1	
				X.XXX	±0.10	SHEET	1/1	CHECK	TITLE:		1.0排母 塑高2.1 2*XXP 双排 180度 U型	
REV	DATE	MODIFICATION	DESCRIPTION	CHANGE	APPROVE	PROJ.	APPROVE	APPROVE	Customer No.			