



Specifications



备注 (Remark)
1. 材料 (MATERIAL)
胶芯: PA6T+30%G. F UL94V-0, 颜色: 黑色.
Housing: PA6T+30%G. F UL94V-0, Color: Black
端子: 磷/青铜, 镍底30u"MIN, 表面镀金1u"MIN
Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL
30u" MIN NICKEL UNDERPLATING OVER ALL
2. 特性 (characteristics):
额定电流: 3 AMP
Raring Current: 3 AMP.
接触阻抗: 20 mΩ MAX.
Contact Resistance: 20 mΩ MAX.
绝缘阻抗: 1000 MΩ MIN.
Insulating Resistance: 1000 MΩ MIN.
耐电压: AC 500V.
Withstanding Voltage: AC 500V.
温度范围: -40° C to +105° C
Temperture Range: -40° C to +105° C



Ordering Information

B0736-12 XX XX X CU X 2

NO. OF PINS	Contact Plating		INSULATOR	PACKING
PER ROW	Full Of Gold	Semi-gold	MATERIAL:	A:PE Bag
2`50P	G0=0.8u`	L0=0.8U`	1:PBT	B:Tape & Reel
	G1=1u`	L1=1U`	2:PA46	C:Tube
	G2=1.5u`	L2=1.5U`	3:PA66	D:Tube+CAP
	G3=2u`	L3=2U`	4:PA6T	E:Tray
	G4=3u`	L4=3U`	5:PA9T	
	G5=5u`	L5=5U`	6:LCP	
	G6=10u`	L6=10U`	7:	
	G7=15u`	L7=15U`		
	G8=20u`	L8=20U`		
	G9=30u`	L9=30U`		
	T1=Ordinary Tin Plated			
	T2=Matte Tin Plated			
	T3=Tin-plated High-temperature			
	T4=high temperture Matt tin			



						OPERATION		SCALE		Fit	苏州瀚牧锦电子有限公司			
						X.X	±0.25	UNIT		MM				
						X.XX	±0.20	SIZE	A4	DESIGN		PART NO.	B0736-12XXXXXCUX2	
						X.XXX	±0.10							
						Angle	±3°	SHEET	1/1	CHECK		TITLE:	2.54mm 双排母 塑高3.5 SMT 带柱 U型	
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	DIM	TOL	PROJ.		APPROVE		Customer No.	