

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T/PBT+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T/PBT+30%G.F UL94V-0, Color: Black

端子: 磷/青铜, 镍底30u"MIN, 表面镀金1u"MIN

Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 3 AMP

Raring Current: 3 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.


Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40° C to +105° C


Temperture Range: -40° C to +105° C



Ordering Information

B0785-11 XX XX X BY X 1

NO. OF PINS PER ROW	Contact Plating		INSULATOR	PACKING
	Full Of Gold	Semi-gold		
2~50P	G0=0.8u"	L0=0.8U"	1: PBT	A: PE Bag
	G1=1u"	L1=1U"	2: PA46	B: Tape & Reel
	G2=1.5u"	L2=1.5U"	3: PA66	C: Tube
	G3=2u"	L3=2U"	4: PA6T	D: Tube+CAP
	G4=3u"	L4=3U"	5: PA9T	E: Tray
	G5=5u"	L5=5U"	6: LCP	
	G6=10u"	L6=10U"	7:	
	G7=15u"	L7=15U"		
	G8=20u"	L8=20U"		
	G9=30u"	L9=30U"		
	T1=Ordinary Tin Plated			
	T2=Matte Tin Plated			
	T3=Tin-plated High-temperature			
	T4=high temperture Matt tin			



					OPERATION		SCALE		Fit	苏州瀚牧锦电子有限公司			
					X.X	±0.25	UNIT		MM				
					X.XX	±0.20	SIZE	A4	DESIGN		PART NO.	B0785-11XXXXBYX1	
					X.XXX	±0.10							
					Angle	±3°	SHEET	1/1	CHECK		TITLE:	2.54mm 单排母 塑高8.5 90度 Y型	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	APPROVE	DIM	TOL	PROJ.		APPROVE	Customer No.		