


Specifications


备注(Remark)
1. 材料(MATERIAL)
胶芯: PA6T/PBT+30%G.F UL94V-0, 颜色: 黑色.
Housing: PA6T/PBT+30%G.F UL94V-0,Color: Black
端子: 磷/青铜, 镍底30u”MIN, 表面镀金u”MIN
Contact:Phosphor bronze,lu”MIN GOLD PLATING OVER ALL
30u” MIN NICKEL UNDERPLATING OVER ALL
2. 特性 (characteristics):
额定电流: 3 AMP
Raring Current:3 AMP.
接触阻抗: 20 mΩ MAX.
Contact Resistance:20 mΩ MAX.
绝缘阻抗: 1000 MΩ MIN.
Insulating Resistance:1000 MΩ MIN.
耐电压: AC 500V.
Withstanding Voltage:AC 500V.
温度范围: -40℃ to+105℃
Temperture Range: -40℃ to+105℃



Ordering Information

B0757-11 XX XX X AY X 1

NO. OF PINS PER ROW	Contact Plating		INSULATOR	PACKING
2~50P	Full Of Gold	Semi-gold	MATERIAL:	A:PE Bag
	G0=0.8u”	L0=0.8U”	1:PBT	B:Tape & Reel
	G1=1u”	L1=1U”	2:PA46	C:Tube
	G2=1.5u”	L2=1.5U”	3:PA66	D:Tube+CAP
	G3=2u”	L3=2U”	4:PA6T	E:Tray
	G4=3u”	L4=3U”	5:PA9T	
	G5=5u”	L5=5U”	6:LCP	
	G6=10u”	L6=10U”	7:	
	G7=15u”	L7=15U”		
	G8=20u”	L8=20U”		
	G9=30u”	L9=30U”		
	T1=Ordinary Tin Plated			
	T2=Matte Tin Plated			
	T3=Tin-plated High-temperature			
	T4=high tempreture Matt tin			



				OPERATION		SCALE		Fit	苏州瀚牧锦电子有限公司	
				X.X	±0.25	UNIT		MM		
				X.XX	±0.20	SIZE	A4	DESIGN	PART NO.	B0757-11XXXXXAYX1
				X.XXX	±0.10	SHEET	1/1	CHECK	TITLE:	2.54mm 单排母 塑高5.7 180度 Y型
REV	DATE	MODIFICATION	DESCRIPTION	CHANGE	APPROVE	PROJ.	APPROVE	Customer No.		
1		2	3	4	5	6	7	8	9	10