

1 2 3 4 5 6 7 8 9 10

Specifications

A 备注(Remark)

1. 材料(MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 磷/青铜, 镍底30μ"MIN, 表面镀金10μ"MIN

Contact: Phosphor bronze, 10μ"MIN GOLD PLATING OVER ALL
30μ" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 3 AMP

额定电流: 3 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.





Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C



Ordering Information

B0735-11 XX XX X AY X 1

NO. OF PINS PER ROW	Contact Plating	INSULATOR	PACKING
2~50P	Full Of Gold	Semi-gold	MATERIAL:
	G0=0.8"	L0=0.8U"	1:PBT
	G1=1u"	L1=1U"	2:PA46
	G2=1.5u"	L2=1.5U"	3:PA66
	G3=2u"	L3=2U"	4:PA6T
	G4=3u"	L4=3U"	5:PA9T
	G5=5u"	L5=5U"	6:LCP
	G6=10u"	L6=10U"	7:
	G7=15u"	L7=15U"	
	G8=20u"	L8=20U"	
	G9=30u"	L9=30U"	

T1=Ordinary Tin Plated

T2=Matte Tin Plated

T3=Tin-plated High-temperature

T4=high temperature Matt tin

苏州瀚牧锦电子有限公司

REV	DATE	MODIFICATION	DESCRIPTION	CHANGE	APPROVE	OPERATION		SCALE		Fit		SIZE	A4	DESIGN	PART NO.	TITLE:	Customer No.
						DIM	TOL	UNIT	MM	PROJ.	APPROVE						
1	2	3	4	5	6	X.X	±0.25										
						X.XX	±0.20										
						X.XXX	±0.10										
						Angle	±3°										
						SHEET	1/1	CHECK									
						PROJ.	APPROVE										

1 2 3 4 5 6 7 8 9 10