


Specifications


备注 (Remark)
1. 材料 (MATERIAL)
胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色.
Housing: PA6T+30%G.F UL94V-0, Color: Black
端子: 磷铜, 镍底30u"MIN, 表面镀金1u"MIN
Contact: Phosphor, 1u"MIN GOLD PLATING OVER ALL
30u" MIN NICKEL UNDERPLATING OVER ALL
2. 特性 (characteristics):
额定电流: 1 AMP
Rating Current: 1 AMP.
接触阻抗: 20 mΩ MAX.
Contact Resistance: 20 mΩ MAX.
绝缘阻抗: 1000 MΩ MIN.
Insulating Resistance: 1000 MΩ MIN.
耐电压: AC 500V.
Withstanding Voltage: AC 500V.
温度范围: -40° C to +105° C
Temperture Range: -40° C to +105° C



Ordering Information

B0343-11 XX XX X CU X 1

NO. OF PINS PER ROW	Contact Plating		INSULATOR	PACKING
2~50P	Full Of Gold	Semi-gold	MATERIAL:	A: PE Bag
	G0=0.8u"	L0=0.8u"	1: PBT	B: Tape & Reel
	G1=1u"	L1=1u"	2: PA46	C: Tube
	G2=1.5u"	L2=1.5u"	3: PA66	D: Tube+CAP
	G3=2u"	L3=2u"	4: PA6T	E: Tray
	G4=3u"	L4=3u"	5: PA9T	
	G5=5u"	L5=5u"	6: LCP	
	G6=10u"	L6=10u"	7:	
	G7=15u"	L7=15u"		
	G8=20u"	L8=20u"		
	G9=30u"	L9=30u"		
	T1=Ordinary Tin Plated			
	T2=Matte Tin Plated			
	T3=Tin-plated High-temperature			
	T4=high temperture Matt tin			



						OPERATION		SCALE		Fit	苏州瀚牧锦电子有限公司			
						X.X	±0.25	UNIT		MM				
						X.XX	±0.20	SIZE	A4	DESIGN		PART NO.	B0343-11XXXXXCUX1	
						X.XXX	±0.10							
						Angle	±3°	SHEET	1/1	CHECK		TITLE:	1.27mm 单排母 塑高4.3 SMT U型 正脚位	
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	DIM	TOL	PROJ.		APPROVE		Customer No.	